



- **Integrated float switch:** makes the pump suitable for limited spaces.
- **Manual and automatic working**
- **Minimum draining level 2mm (man)**
- **Integrated check valve**

Model: **COMPAC 150**  
 Part number: **N1080030**  
 Barcode: **8010583317176**

Submersible pump for clear water. Motor shaft in stainless steel, single phase NORYL hydraulic system. COMPAC pumps are equipped with 10 m power cable with plug and can be used in manual or automatic version with float switch.



### APPLICATIONS

Drainage of standing water and domestic waste water  
 Flooded rooms emptying and drying  
 Water drawing from wells, basins or cisterns

<b>ABSORBED POWER</b>	300 W	<b>MAX TEMP. OF PUMPED FLUID</b>	40°C
<b>VOLTAGE</b>	230 V	<b>MAX.SIZE OF IMPURITIES</b>	5 mm
<b>FLOW RATE</b>	8500 l/h	<b>START/STOP</b>	140 mm / 30 mm
<b>MAX. HEAD</b>	7 m	<b>WEIGHT</b>	4.7 kg
<b>PUMP BODY</b>	Polypropylene	<b>PACKAGING DIMENSIONS</b>	23 x 19.5 x 29 cm
<b>PUMP OUTLET DIAMETER</b>	41,90 mm (1 1/4 M)	<b>PCS PER PALLET</b>	60
<b>MIN. DRAINING LEVEL</b>	2 mm / 30 mm (man/aut)	<b>ACCESSORIES</b>	Adjustable connector/ check valve
<b>MAX DEPTH OF IMMERSION</b>	7 m		



- **Integrated float switch:** makes the pump suitable for limited spaces
- **Manual and automatic working**
- **Minimum draining level 2mm (man)**
- **Integrated check valve**

Model: **COMPAC 200**  
 Part number: **N1080040**  
 Barcode: **8010583317183**

Submersible pump for clear water. Motor shaft in stainless steel, single phase NORYL hydraulic system. COMPAC pumps are equipped with 10 m power cable with plug and can be used in manual or automatic version with float switch.



#### APPLICATIONS

Drainage of standing water and domestic waste water.  
 Flooded rooms emptying and drying  
 Water drawing from wells, basins or cisterns

<b>ABSORBED POWER</b>	650 W	<b>MAX TEMP. OF PUMPED FLUID</b>	40°C
<b>VOLTAGE</b>	230 V	<b>MAX.SIZE OF IMPURITIES</b>	5 mm
<b>FLOW RATE</b>	11500 l/h	<b>START/STOP</b>	140 mm / 30 mm
<b>MAX. HEAD</b>	10 m	<b>WEIGHT</b>	4.7 kg
<b>PUMP BODY</b>	Polypropylene	<b>PACKAGING DIMENSIONS</b>	23 x 19.5 x 29 cm
<b>PUMP OUTLET DIAMETER</b>	41,90 mm (1 1/4 M)	<b>PCS PER PALLET</b>	60
<b>MIN. DRAINING LEVEL</b>	2 mm / 30 mm (man/aut)	<b>ACCESSORIES</b>	Adjustable connector/ check valve
<b>MAX DEPTH OF IMMERSION</b>	7 m		